

STAMFORD® S6



700 - 1,695 kVA

Model	S6
Maximum continuous rating at 50Hz (kVA)	1,400
Maximum continuous rating at 60Hz (kVA)	1,695

Specifications	
Voltage Range	380-690
Poles	4
Technology	Wire Wound
AVR	Analogue
Voltage sensing	3-Phase
Bearing Arrangement	Single
SAE Adaptors	0, 00, 1
Terminals	6
Material Insulation Class	H
Excitation System	PMG
Ingress Protection	IP23
Connection with other machines	Paralleling capability

Optional Features	
Bearing Arrangement	Double
Ingress Protection	IP23 Air Filters
Ingress Protection	IP44 Air Filters
AVR	Digital
Temperature monitoring	Winding RTDs
Temperature monitoring	Thermistors
Environmental protection	Anti-condensation Heaters
Ingress Protection	IP44

Designed For	
Grid Code Compatible	●
Marine Auxiliary	●
Oil & Gas	●
Oil & Gas Auxiliary	●
Combined Heat & Power	●
Critical Protection & UPS	●
Continuous Power & Standby	●

Prime Movers	
Diesel Engine	●
Gas Engine	●

3 YEAR WARRANTY

DIMENSIONS

*Drawings represent standard design
All dimensions in millimetres (mm)*

